ASPHALT ANCHORS

EPX2 ANCHORING CEMENT
LOWEST COST

SET ANCHORS FOR LESS.

EPX2 is a rapid-setting, expanding anchoring cement, much like fence-post cement. Poured into a clean, dry hole, it bonds the anchor to the asphalt and the gravel below. It suits dry, planned jobs with a crew: one person mixing, one pouring, one setting anchors.



Under 10 min	About 2 hr	40°F +	Dry only
WORK TIME at 75°F	**READY TO LOAD** sets in 15 min; at 75°F	**INSTALL TEMPERATURE** warm water below 50°F	**HOLE CONDITION** no rain or standing water

USE EPX2 WHEN

- The holes and pavement are dry
- It's 40°F or warmer
- Material cost matters most
- You have hands to mix, pour and set without rushing

CHOOSE EPX3 INSTEAD when holes are damp or wet, it's below 40°F, or you want the simplest install.

HOW TO USE

1. **CLEAN.** Brush the full depth with a brush on a drill, blow out, and repeat. Holes must be dry.
2. **MIX.** Water first, then add powder while stirring, to a syrup-like mix. Mix for at least 4 anchors at a time.
3. **POUR.** Fill each hole about 2/3 full before the mix starts to set.
4. **SET.** With its bolt still threaded in, push the anchor in with a slow up-and-down motion until flush. Clean off the squeeze-out right away.
5. **WAIT.** Load after about 2 hours at 75°F, longer in the cold.

ORDERING

PART NUMBER	DESCRIPTION
82-5002.K	EPX2, 6 × 12 oz bags
ADH-EPX2TUB2P5	EPX2, 2.5 lb tub
ADH-EPX2-TUB10LB	EPX2, 10 lb tub

COVERAGE

ANCHOR	PER 6-BAG PACK	PER 2.5 LB TUB	PER 10 LB TUB
SP10	23	12	51
SP12	17	9	38
SP18	13	7	30
SP58	6	3	13

Anchors per package, from the same numbers as the adhesive calculator at asphaltanchors.com. Plan about 20% extra on site.

SPECIFICATIONS

TYPE	Rapid-setting, expanding anchoring cement, mixed with water
PACKAGES	12 oz bags (6-pack), 2.5 lb tub, 10 lb tub
MIX	About 1 part water to 4–5 parts powder; see the package label
TEMPERATURE	Install at 40°F and above; below 50°F use warm mixing water and pour promptly
HOT WEATHER	Keep the mix shaded; set the mixing container in ice water
SHELF LIFE	2 years sealed; use within 3 months of opening

Guide loads for our anchors are the same with EPX2 or EPX3 installed per their instructions. Damtite and QUIKRETE Anchoring Cement are local equivalents. Don't substitute concrete mix, mortar or construction adhesive.

ENGINEERED FOR ASPHALT, BUILT TO HOLD.

Asphalt Anchors Corp. · 10 Ridge Rd, West Orange, NJ 07052
(973) 669-8214 · support@asphaltanchors.com · asphaltanchors.com/products/epx2

BoltHold® is a registered trademark of Asphalt Anchors.